

MONITOR MV3000

4" monochrome monitor, perfectly compatible with the AN 8419 (MV 100) model. Equipped with 'universal' electronics, this monitor is ready to work either in traditional analogue systems or in €-BUS systems upon simple programming using dip switches.

Other main features include:

- Surface-mounted installation (thickness 68mm)
 - Two-tone electronic external call
- Electronic floor call to piezoelectric buzzer; therefore, it can also be used in lieu of AN 8310 (MV 80) monitors
- Integrated, mutable conversation privacy function
 - Adjustable call volume
 - Adjustable contrast and brightness
 - Two function buttons
- Monitor and video unit automatic power-on
 - Door lock release
- Two NO spare buttons for auxiliary services
 - Wall bracket provided
- Connection by way of extractable terminal block
 - Two finish ABS casing: white and grey



Technical features

- Power voltage: 16-21Vdc
 - Drawn current: 500 mA
- A and B video signals: 1.5 Vpp on 75Ω
 - 4" flat screen B/W CRT
- Audio: '1+1' with excludable privacy
- Compatible with run-through ('in-out') installations and video distributors

AV 6000/GR

MV 3000 SILVER monitor, surface mounted and in desk-top version.



CODE	DESCRIPTION
AV 6000	MV3000 in traditional light ABS case
AV 6000/GR	MV3000 SILVER in silver-grey ABS
AN 8641	Plexiglas desk-top base for MV 3000 monitor and its variants