



# VISTA VVR

## VANDAL RESISTANT CAMERA RANGE



### IDEAL FOR APPLICATIONS SUCH AS:

- Prisons
- Schools
- Hospitals
- Car Parks
- Stairwells
- Lifts
- Airports
- Bus Depots
- Railway Stations

### MAIN FEATURES:

- High resolution monochrome and colour camera options
- Discreet design
- 4 -9mm DD varifocal lens
- Wall mount comes with a 3.6mm EI lens
- Vandal resistant housing

### VANDAL RESISTANT CAMERAS

Able to withstand a blow from a 12lb sledgehammer, the Vandal Resistant Camera range from Vista is the ideal surveillance solution for monitoring areas prone to physical attack.

Available in a variety of different housings, the range has been designed to offer continuity in looks and features while delivering diversity in mounting styles and positioning.

The securely encased 4-9mm varifocal direct drive lens (3.6mm EI for wall mounted versions) delivers crystal clear imagery for end users even under the most hostile of conditions. Both high resolution monochrome and colour versions are widely available.



## THE UK'S PREMIER CCTV



## TECHNICAL SPECIFICATIONS

	VVRDF4V9C	VVRD4V9C-LP	VVRD4V9C	VVRCW4V9C	VVRCM4V9C	VVRWM36C
MOUNT	Dome flush	Dome Surface	Dome Surface	Ceiling Wedge	Corner Mount	Wall Mount
SENSOR (CCD)	1/3" CCD					
TYPE	Colour					
RESOLUTION	470 TVL					
SENSITIVITY	2.8 lux with smoked cover, 1.0 lux without cover					
PIXELS	752 x 582					
COMPOSITE OUTPUT	1Vp.p					
SIGNAL TO NOISE RATIO	46dB AGC off					
ELEC. IRIS CONTROL	Off					
BLC	On 40% Cntr					
SHUTTER SPEED	Auto-1/50-1/100,000					
AGC	On					
SYNCHRONISATION	Internal					
GAMMA	On 0.45					
POWER SOURCE	12V DC +/-10%					
POWER CONSUMPTION	Max 2.4W					
WEIGHT	0.45Kg	0.59Kg	0.53Kg	0.97Kg	0.75Kg	0.7Kg
GROSS WEIGHT						
LENS OPTION	4-9 mm DD					3.6 MI
OPERATING TEMP.	-10deg C - 50 deg C					
OPERATING HUMIDITY	10-96% (non-condensing)					
DIMENSIONS (LXWXH)MM	120Dia x 91.5		114Dia x 94.5	172 x 103 x 92	124.2x 104.6 x 120	105 x 120 x 67.5
DIMENSIONS CAMERA	65 x 42 x 42					48 x 42 x 42
CONSTRUCTION	Aluminium					
WINDOW SIZE	86mm		88mm	58mm	40 x 50mm	
	VVRDF4V9M/HR	VVRD4V9M-LP/HR	VVRD4V9M/HR	VVRCW4V9M/HR	VVRCM4V9M/HR	VVRWM36M/HR
MOUNT	Dome flush	Dome Surface	Dome Surface	Ceiling Wedge	Corner Mount	Wall Mount
SENSOR (CCD)	1/3" CCD					
TYPE	Monochrome					
RESOLUTION	570 TVL					
SENSITIVITY	0.08 lux, F1.2					
PIXELS	752 x 582					
COMPOSITE OUTPUT	1Vp.p					
SIGNAL TO NOISE RATIO	48dB AGC off					
ELEC. IRIS CONTROL	Off					
BLC	On 40% Cntr					
SHUTTER SPEED	Auto-1/50-1/100,000					
AGC	On					
SYNCHRONISATION	Internal					
GAMMA	On 0.45					
POWER SOURCE	12V DC +/-10%					
POWER CONSUMPTION	Max 2W					
WEIGHT	0.45Kg	0.59Kg	0.53Kg	0.97Kg	0.75Kg	0.7Kg
GROSS WEIGHT						
LENS OPTION	4-9 mm DD					3.6 MI
OPERATING TEMP.	-10deg C - 50 deg C					
OPERATING HUMIDITY	10-96% (non-condensing)					
DIMENSIONS (LXWXH)MM	120Dia x 91.5		114Dia x 94.5	172 x 103 x 92	124.2x 104.6 x 120	105 x 120 x 67.5
DIMENSIONS CAMERA	65 x 42 x 42 mm					48 x 42 x 42 mm
CONSTRUCTION	Aluminium					
WINDOW SIZE	86mm		88mm	58mm	40 x 50mm	

